

Charging Cabinet Specification

Spec of T-Series Charging Cabinets

No.	Items	Description	Notes
		T30B/40B/T52B/T60B	
1	Product	Charging cabinet	
2	Brand	OEM	
3	Model	T30B/40B/T52B/T60B	
4	Certification	CE, ROHS, REACH	
5	Importer	TBA	
6	USB Port	30/40/52/60 USB ports	
7	Material	Metal Sheet	
8	Color	Light Grey / Black	
9	Structure	Power on left, Tablet on right	
10	Wheel	4pcs, Large Rubber Wheels (The first two wheels to brake)	
11	Max Tablet Size (L*W*H)	310*27.5*212mm	
12	Dimension (L*W*H)	T30B: 556*400*920mm, T40B: 560*400*1190mm, T52B: 650*400*1190mm, T60B: 650*400*1450mm	
13	Weight	43kg / 57kg / 56 kg / 61 kg	
14	Lock	Ordinary lock with a key	
15	Input voltage	220 V	
16	Input power	415 W / 600 W / 800 W / 900 W	
17	USB Output	Each USB Port 5V / 2A	
18	USB charging	Constant current and limited voltage to protect devices.	
19	LED condition	Red when charging, green when not charging or full charge	
20	Over heat protection	65±5 °C	
21	Time display	When the AC power supply is on, time will be always displayed	
22	UV disinfection system	Cabinet has a UVGI (UV Germicidal Irradiation) disinfection system that uses UV C light to kill micro-organisms. No chemicals is used for the disinfection protecting the devices and keeping them clean from bacteria and viruses.	
23	UV switch of disinfection	Controlled through Control Panel, Will Switch off if the cabin door is opened. Cabin door window is UV protected keeping UV C radiation inside. Disinfection time 1 - 5 minutes. Safe for devices and humans.	
24	Smart cooling fan	2 pcs of cooling fans, Fans will start-up automatically when cabin temperature reached 50 degrees	
25	Ground wire	1 PC	

Charging Cabinet Specification

26	Included	Manual, Charging cables 40 pcs, Key for the power source, 2x cabinet keys for the front door lock	
Above product specification is for reference only, Any discrepancy in future, pls adhere to the actual product instead			